PRO BİTÜM 1K

Elastomerik Reçine Esaslı
Kullanıma Hazır %400 Elastik
Su Yalıtım Malzemesi

Tanımı

- Tek bileşenli, bitüm emülsiyon esaslı polimer modifiyeli, kullanıma hazır, süper elastik, toprak altında kalan yapıları suyun pozitif yönden gelen zararlı etkilerine karşı koruyan su yalıtım malzemesi.

Kullanım Alanları

- Yapıların temel, perde duvarlarında toprak altında kalan sürekli su ile temas eden yatay ve düşey zeminlerde.
- Dam, balkon, çatı ve teraslarda seramik fayans ve şap altında.
- Islak hacimli mekanlarda su yalıtımında.
- Eski su yalıtım kaplamalarının tamiratlarında.
- Sızıntı suyuna ve yeraltı sularına karşı su yalıtım uygulamalarında kullanılır.

Avantaj ve Özellikleri

- Bitki ve köklerine karşı dayanıklıdır. Kılcal çatlakları kapatır.
- Kullanıma hazır. Fırça, rulo ve havasız sprey makinaları ile rahat uygulanır.
- Yanıcı ve zehirli madde içermediği için kapalı alanlarda kullanılabilir su bazlı olduğu için çevre dostudur.
- Ağır hava koşulları ve kimyasallara karşı dayanıklıdır.
- Aderansı yüksek, kalıcı ve yüksek elastikiyete sahiptir. Elastik özelliğinden dolayı sıcaklık farklarına karşı dayanıklıdır.

Definition

- Single component, bitumen emulsion based polymer modified, ready to use, super elastic, waterproofing material that protects underground structures against the positive harmful effects of water.

Areas of Use

- In horizontal and vertical surfaces that are constantly in contact with water, such as foundations and curtain walls of buildings.
- Under ceramic tiles and screeds on roofs, balconies, attics and terraces.
- Waterproofing in wet areas.
- In repairs of old waterproofing coatings.
- It is used in waterproofing applications against seepage water and groundwater.

Advantages and Features

- It is resistant to plants and their roots. It closes capillary cracks.
- Ready to use. Easily applied with brush, roller and airless spray machines.
- It can be used in closed areas because it does not contain
- flammable or toxic substances and is environmentally friendly because it is water-based.
- Resistant to harsh weather conditions and chemicals.
- It has high adherence, permanent and high elasticity. It is resistant to temperature differences due to its elastic feature.